

L216

Industrial grade module

L216 is a Quad-band (850/900/1800/1900) module with low-power consumption, high performance . It combines GNSS technology with high-sensitivity receiver. Its LCC package make it easy to be soldered and produced quickly through standard SMT equipment, which adapts to the application that strictly requires cost effectiveness and efficiency.

L216 is capable of fast-positioning, build-in TCP/IP protocol, tiny package and wide work temperature. All of these make it suitable to dimension-sensitive devices and application scenarios of location.



Quad-band



GPRS Class 12




Extended Temperature Range-40°C to +85°C



GNSS



LCC



Ecall



AT命令



Analog Audio



FOTA*



Main Features

- Quad-band: GSM/GPRS 850/900/1800/1900 MHz
- GSM 2/2+ standard
- Class 4 (2W @850/900 MHz)
- Class 1 (1W @1800/1900 MHz)
- AT command: GSM 07.07,07.05 and enhanced AT command
- GNSS: GPS/BEIDOU(GLONASS)
- Voltage range: 3.4 ~ 4.2V (3.8V is recommended)
- Operating temperature range: -40 ~ +85°C
- Storage temperature range: -45 ~ +90°C
- Dimension: 17*19*2.3mm
- Weight: Approx. 1.5g

Specification for Data

- GPRS CLASS 12
- Coding schemes CS 1,2,3,4
- PPP-stack
- Transparent Transmission Mode
- TCP/UDP/HTTP/SMTP*
- USSD

Specification for SMS

- Message
- MO and MT
- Point-to-Point and cell broadcast
- TEXT and PDU mode

Specification for Voice

- Half rate (HR)
- Full rate (FR)
- Enhanced full rate (EFR)
- Adaptive multi-rate (AMR)

Specification for GNSS

- Receiver type
33 tracking/99 acquisition-channel GPS receiver
- Max update rate: 10Hz
- Sensitivity
Tracking: -165dBm
Reacquisition: -160dBm
Cold starts: -148 dBm
- Time-TO-First-FIX:
Cold starts: 31s(typical)
Warm starts: 26s
Hot Starts: <1s
EPO Assist: 13s(CTTFF)
- Accuracy
Automatic Position: 2.5m CEP
Speed: 0.1m/s

Interfaces

- Analog voice
- UART
- I2C
- SIM card(3V/1.8V)
- ADC
- GPIO
- USB
- Charging management
- GSM antenna
- GNSS antenna

Other features

- FOTA*
- ECALL
- TTS*

Certification

- CCC/TA/CE

